


### Product Group OVL/GD

Lamella plugs for flat oval tubes with convex lid




#### Standard Colours

- black RAL 9005

#### Material

- Polyethylene (PE)



### Product information

- The plugs are intended for use in pipes or equivalent bores with free passage corresponding to the clear nominal width of at least shaft length.
- For technical production reasons, a residual sprue may exceed the shaft length.
- Material and design of shafts guaranteed stop against drop out and easy assembling.
- For use as a slides (conditional shear strength) and to attain an easy assembling in tubes with larger wall thickness, it is recommended to chamfer the inside diameter of the pipe (approx. 0.3 - 0.5 x 60°).
- Depending on the selected article, the surface finish can vary between polished and eroded.
- The ribs are circularly closed or interrupted.
- They are not suitable for sealing against fluids.
- The number of slats per plug varies between 2-4 slats.
- GD = cambered top (like series SRL)
- Your searched size / design is not included? - Please ask our sales team!
- As a rule, odd outside pipe diameters rounded to 1/10 mm (as part of the article or order number) indicate that these sizes originate from or are common in the Imperial system.

### Product options on inquiry

- Special colours (colours, minimum quantities, set-up costs, pricing and surcharges)
- With your engraved company logo (tooling costs, minimum quantities, set-up costs)
- With your tampon printed company logo (set-up costs, minimum quantities, printing costs)
- Most plugs can also be made of suitable harder TPE's (TPE= thermoplastic elastomer --> extended range of operating temperature, noise absorbing, non-skid).

| Order Number          | A  | B  | H  | H1 | L    | t       |
|-----------------------|----|----|----|----|------|---------|
|                       | mm | mm | mm | mm | mm   | mm      |
| OVL 20x10x0,75-2 GD   | 20 | 10 | 3  | 3  | 11,5 | 0,75-2  |
| OVL 25x10x0,8-2 GD    | 25 | 10 | 3  | 3  | 11,5 | 0,8-2   |
| OVL 30x10x0,8-2 GD    | 30 | 10 | 3  | 3  | 11,5 | 0,8-2   |
| OVL 30x15x1,5-2 GD    | 30 | 15 | 4  | 3  | 16   | 1,5-2   |
| OVL 35x15x0,8-2,5 GD  | 35 | 15 | 4  | 3  | 11,5 | 0,8-2,5 |
| OVL 35x20x1-3 GD      | 35 | 20 | 5  | 3  | 11,5 | 1-3     |
| OVL 38x20x1,5 GD / 20 | 38 | 20 | 5  | 3  | 20   | 1,5     |
| OVL 38x20x1-3 GD      | 38 | 20 | 5  | 3  | 11,5 | 1-3     |
| OVL 40x20x0,8-2,5 GD  | 40 | 20 | 5  | 3  | 11,5 | 0,8-2,5 |
| OVL 48x20x1-2,5 GD    | 48 | 20 | 5  | 3  | 11,5 | 1-2,5   |



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

| Order Number         | A  | B  | H  | H1  | L    | t       |
|----------------------|----|----|----|-----|------|---------|
|                      | mm | mm | mm | mm  | mm   | mm      |
| OVL 50x20x1-3 GD     | 50 | 20 | 5  | 3   | 11,5 | 1-3     |
| OVL 50x25x1-3 GD     | 50 | 25 | 3  | 3   | 11,5 | 1-3     |
| OVL 50x30x1-3 GD     | 50 | 30 | 5  | 3   | 11,5 | 1-3     |
| OVL 60x20x0,8-2,5 GD | 60 | 20 | 5  | 3   | 11,5 | 0,8-2,5 |
| OVL 60x30x1,5-2 GD   | 60 | 30 | 8  | 3,5 | 13,5 | 1,5-2   |
| OVL 70x40x1-3 GD     | 70 | 40 | 5  | 3   | 14,5 | 1-3     |
| OVL 80x25x1,2-2,5 GD | 80 | 25 | 5  | 3   | 14,5 | 1,2-2,5 |