




### Product Group MFSSR

Machine feet made of stainless steel with vulcanized rubber pad



#### Material

- Base body: AISI 304 (A2)
- Rubber: NBR 80 Shore, vulcanized



#### Product information

- Depending on the size of the thread or the foot diameter, the machine foot is provided with a chamfer on both sides or with a hexagon as a spanner flat.
- The foot is made of pressed moulded sheet metal. The vulcanized rubber is firmly attached to the sheet. This prevents the penetration of bacteria and ensures a high standard of hygiene.
- Die abgerundete Form und der verdeckte Übergang vom Fuß zum Gewinde erleichtern die Reinigung.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Food industry

#### Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)

| D   | F max. | H  | H1   | M   | WAF | 50 | 75 | 100 | 125 | 150 | 175 | 200 | 225 | 250 |
|-----|--------|----|------|-----|-----|----|----|-----|-----|-----|-----|-----|-----|-----|
| mm  | kg     | mm | mm   |     | mm  | mm | mm | mm  | mm  | mm  | mm  | mm  | mm  | mm  |
| 50  | 400    | 19 | 29   | M10 | 14  | x  | x  | x   | x   |     |     |     |     |     |
| 50  | 400    | 19 | 29   | M12 | 14  | x  | x  | x   | x   |     |     |     |     |     |
| 50  | 400    | 19 | 29   | M14 | 14  |    | x  | x   | x   | x   |     |     |     |     |
| 50  | 400    | 19 | 34   | M16 | 13  |    | x  | x   | x   | x   |     |     |     |     |
| 80  | 1000   | 25 | 35   | M14 | 14  | x  | x  |     |     | x   | x   |     |     |     |
| 80  | 1000   | 25 | 35   | M10 | 14  |    | x  | x   |     |     |     |     |     |     |
| 80  | 1000   | 25 | 35   | M12 | 14  |    |    | x   | x   |     |     |     |     |     |
| 80  | 1000   | 25 | 35   | M16 | 13  |    | x  | x   | x   | x   | x   |     |     |     |
| 80  | 1000   | 25 | 38   | M20 | 17  |    | x  | x   | x   | x   | x   | x   | x   |     |
| 80  | 1000   | 25 | 40   | M24 | 20  |    | x  | x   | x   | x   | x   | x   | x   |     |
| 100 | 1500   | 30 | 39,5 | M16 | 13  |    | x  | x   | x   | x   | x   | x   |     |     |
| 100 | 1500   | 30 | 43   | M20 | 17  |    | x  | x   | x   | x   | x   | x   | x   | x   |
| 100 | 1500   | 30 | 44   | M24 | 20  |    |    | x   | x   | x   | x   | x   | x   | x   |
| 100 | 1500   | 30 | 44   | M30 | 26  |    |    | x   | x   | x   | x   | x   | x   | x   |
| 120 | 3000   | 32 | 47   | M16 | 13  |    | x  | x   | x   | x   | x   |     |     |     |
| 120 | 3000   | 32 | 47   | M20 | 17  |    | x  | x   | x   | x   | x   | x   | x   | x   |
| 120 | 3000   | 32 | 47   | M24 | 20  |    |    | x   | x   | x   | x   | x   | x   | x   |
| 120 | 3000   | 32 | 49   | M30 | 26  |    |    | x   | x   | x   | x   | x   | x   | x   |



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

## Ordering example

• Group + D + M + Thread Length ----> MFSSR 50 M10x 50